



CARBON DIOXIDE

CARBON DIOXIDE is discharged as a white cloud of “snow,” which smothers a fire by displacing oxygen. It is effective for Class B flammable liquids and is electrically non-conductive. Carbon Dioxide is a clean, non-contaminating, odorless gas.



322NM
P/N 17738

◀ These DOT-approved shells have date stamped on cylinder shoulder.



322
P/N 01712

330
P/N 01714

331
P/N 01703

332
P/N 01708

RUGGED

- 5-Year manufacturer’s warranty
- All-metal valve construction
- Rust-free aluminum cylinders
- Durable high-gloss polyester powder paint
- Temperature range -22°F to 120°F

USER-FRIENDLY

- Meets many hospital medical equipment requirements
- Large loop stainless steel pull pin
- QR coded and multilingual labels
- Leaves no residue

OPTION

- USCG approved with bracket listed on UL label
- Model 322NM is independently tested and approved for use in MRI facilities to 11.7 Tesla
- Model 322NM has a sanitary white paint finish (easy to clean)

AVAILABLE IN 50- AND 100-LB. WHEELED EXTINGUISHERS

NONMAGNETIC MODEL AVAILABLE (MODEL 322NM—TESTED TO 11.7 TESLA)

322NM ONLY

MR CONDITIONAL

THIS EXTINGUISHER HAS BEEN TESTED TO OPERATE PROPERLY AND POSE NO SAFETY HAZARD IN AN MRI ENVIRONMENT ASSOCIATED WITH MR SYSTEMS OPERATING AT 11.7 TESLA OR LESS.

MANUFACTURED AND TESTED TO UL STANDARDS

COMPLIES WITH NFPA 10 STANDARD
ISO-9001/ ISO-14001 CERTIFIED
UL LISTED

CONFORMS TO TEST STANDARDS:

CAN/ULC-S503 - UL 154 &
CAN/ULC-S508 - UL 711

| AGENT TYPE | CARBON DIOXIDE | | | | |
|------------------------------|---------------------|--------------|-------------|------------|------------|
| VALVE TYPE | Chrome-Plated Brass | | | | |
| DESIGN | Tube & Horn | | Hose & Horn | | |
| MODEL NUMBER | 322 | 322NM | 330 | 331 | 332 |
| UL & ULC RATING | 5B:C | 5B:C | 10B:C | 10B:C | 10B:C |
| CAPACITY (LBS.) | 5 | 5 | 10 | 15 | 20 |
| *SHIPPING WT. (LBS.) | 13.1 | 13.1 | 28.25 | 37.75 | 50.75 |
| HEIGHT (IN.) | 17.75 | 17.75 | 24 | 30 | 30 |
| WIDTH (IN.) | 8.25 | 8.25 | 12 | 12 | 13 |
| DEPTH (IN.) | 5.25 | 5.25 | 7 | 7 | 8 |
| RANGE (INITIAL- FT.) | 3-8 | 3-8 | 3-8 | 3-8 | 3-8 |
| DISCHARGE TIME (SEC.) | 9 | 9 | 11 | 14.5 | 19.2 |
| INCLUDED BRACKET | Wall | NM Wall | Wall | Wall | Wall |

*Shipping weight includes box.

