

HT-SERIES



551
P/N 28084

MODEL 551 Once exclusive to the aerospace industry, the high performing HT-Series for commercial settings can safely put out fires without damaging electronic equipment, specialized machinery, or other delicate materials. That also means that there is no clean-up or down time for your operations. Industries such as health care, clean manufacturing, data processing centers, and museums would all benefit from the HT Series. This fire extinguisher is also sensitive to the environment, meeting strict environmental regulations for Global Warming Potential and Ozone Depletion Potential. With knock down power and firefighting efficiency, the HT-Series using Halotron BrX agent features a steel cylinder, durable high-gloss polyester powder paint, and all-metal valve construction. Maximum visibility during discharge, a large stainless steel pull pin, and no electronic conductivity back to the user make this extinguisher extremely easy to use.

Get **MORE FIGHTING POWER** with **LESS AGENT**



RUGGED

- 6-Year manufacturer's warranty
- 12-year service life; non-rechargeable
- Stored-pressure design for simple inspection
- Durable, high-gloss polyester powder-coat finish
- All-metal valve construction
- Steel cylinder design
- 7-day atmospheric lifespan
- A low-GWP and very low-ODP product
- Temperature range -40°F to 120°F

USER-FRIENDLY

- Leaves no residue
- No thermal or static shock
- Flexible hose, all-metal hose for easy use
- QR coded and multilingual labels

MANUFACTURED AND TESTED TO UL STANDARDS
COMPLIES WITH NFPA 10 STANDARD
ISO-9001 AND ISO-14001 CERTIFIED
UL LISTED

CONFORMS TO TEST STANDARDS:
CAN/ULC-S508 - UL 2129 &
CAN/ULC-S566 - UL 711

PREMIUM PRODUCT FOR HIGHLY TECHNICAL ENVIRONMENTS

AGENT TYPE	HALOTRON® BrX (2-BTP)
VALVE TYPE	Anodized Aluminum
DESIGN	Hose & Nozzle
MODEL NUMBER	551
UL & ULC RATING	2A:10B:C
CAPACITY (LBS.) / (KG)	12.5 / 5.67
*SHIPPING WT. (LBS.) / (KG)	20 / 9.07
HEIGHT (IN.) / (MM)	20.25 / 514.3
WIDTH (IN.) / (MM)	8.5 / 215.9
DEPTH (IN.) / (MM)	5 / 127
RANGE (INITIAL- FT. / M)	15-17 / 4.57-5.18
DISCHARGE TIME (SEC.)	16
MINIMUM CONFINED SPACE REQUIREMENTS (FT ³ / M ³)	2,988 / 84.6
NOMINAL OPERATING PRESSURE	150 PSIG
INCLUDED BRACKET	Wall

*Shipping weight includes box.

