



HIGH-FLOW DRY CHEMICAL

HIGH-FLOW portable fire extinguishers are for applications where discharge rates exceeding one pound per second are required as specified in NFPA 10. These extinguishers utilize the same hardware and are manufactured to the same UL specifications as Amerex compliance-rated products.



10 LBS (20 LBS)
720 722
P/N 20895 P/N 20899

(10 LBS) 20 LBS
760 762
P/N 20901 P/N 20905



RUGGED

- 6-Year manufacturer's warranty
 - Stored-pressure design
 - Dependable drawn-steel cylinders
 - Durable high-gloss polyester powder paint
 - All-metal valve construction
- BRASS VALVE—Heavy Duty**
- Chrome-plated brass valve body
 - Stainless steel handle & lever
- Twice the flow rate of standard models
 - Meets DOT requirements
 - Temperature range -65°F to 120°F

USER-FRIENDLY

- Easy and economical to maintain and service
- Large loop stainless steel pull pin
- QR coded and multilingual labels

OPTION

- USCG approved with bracket listed on UL label
- ABC or Purple K Chemical

HIGH-FLOW—EXCEEDS 1 LB. PER SECOND DISCHARGE RATE

AGENT TYPE	ABC	ABC	PURPLE K	PURPLE K
MODEL NUMBER	720	760	722	762
DESIGN	Hose & Nozzle		Hose & Nozzle	
CAPACITY (LBS.)	10	20	10	20
UL RATING	1A:20B:C	4A:60B:C	20B:C	60B:C
*SHIPPING WEIGHT (LBS.)	19.5	38	19.5	38
DISCHARGE TIME (SEC.)	10	19	12	20
DISCHARGE RATE (LBS./SEC.)	1.22	1.14	1.15	1.08
DISCHARGE RANGE (FT.)	15-25	15-25	15-25	15-25
HEIGHT (IN.)	20 ½	24	20½	24
WIDTH (IN.)	8 ¾	10 ¼	8¾	10¼
DEPTH (IN.)	5	7	5	7
NOMINAL OPERATING PRESSURE	195 PSIG	195 PSIG	195 PSIG	195 PSIG
INCLUDED BRACKET	Wall		Wall	

*Shipping weight includes box.

MANUFACTURED AND TESTED TO UL STANDARDS
COMPLIES WITH NFPA 10 STANDARD
ISO-9001/ISO-14001 CERTIFIED
UL LISTED

CONFORMS TO TEST STANDARDS:
CAN/ULC-S504 - UL 299 &
CAN/ULC-S508 - UL 711

