

Z-SERIES HIGH PERFORMANCE



Z-Series extinguishers are the ultimate choice in fire extinguishers for high hazard, frequent use, and extreme environment applications. They are economical—less initial cost, lower maintenance costs, and greater reliability than cartridge-operated extinguishers. Amerex Z-Series extinguishers are available with a proprietary, zinc-enriched coating that resists corrosion for up to 12 years in severely salt-contaminated environments.

RUGGED

- 12-Year manufacturer's warranty
- Zinc-enriched coating
- All-metal valve construction
- Chrome-plated brass gauge guards
- Protective rubber foot rings
- Superior vertical and horizontal range
- Higher operating pressure
- Temperature range -65°F to 120°F

AGENTS

- ABC or Purple K

USER-FRIENDLY

- Wide grip allows clearance for gloved hands
- Large loop stainless steel pull pin
- QR coded and multilingual labels

FAST FLOW

- High flow rate
- Fast discharge
- Quicker knockdown
- More operator protection

COMPLIANCE FLOW

- Long range
- Highest UL ratings

OPTION

- USCG approved with bracket listed on UL label
- Hot-dip galvanized USCG brackets available



711

712

FAST FLOW

- 790 P/N 26903
- 791 P/N 26904
- 792 P/N 26905
- 793 P/N 26908
- 794 P/N 26909
- 795 P/N 26910
- 796 P/N 26911

COMPLIANCE FLOW

- 711 P/N 27940
- 712 P/N 28173
- 713 P/N 26912
- 714 P/N 26913
- 715 P/N 26914
- 716 P/N 26915
- 717 P/N 26916
- 718 P/N 26917



AVAILABLE IN 125-AND 250-LB. WHEELED EXTINGUISHERS

MANUFACTURED AND TESTED TO UL STANDARDS

COMPLIES WITH NFPA 10 STANDARD ISO-9001 AND ISO-14001 CERTIFIED UL LISTED

CONFORMS TO TEST STANDARDS:

CAN/ULC-S504 - UL 299 & CAN/ULC-S508 - UL 711

AFFORDABLE AND EASY TO MAINTAIN

| AGENT TYPE | ABC DRY CHEMICAL | | | | PURPLE K DRY CHEMICAL | | | | ABC DRY CHEMICAL | | | | PURPLE K DRY CHEMICAL | | | |
|--------------------------------------|--------------------------------------|----------|-----------|----------|-----------------------|----------|-----------|----------|------------------|------------|------------|----------|-----------------------|----------|-----------|--|
| PERFORMANCE | Fast Flow | | | | | | | | Compliance Flow | | | | | | | |
| VALVE TYPE | Chrome-Plated Brass with Gauge Guard | | | | | | | | | | | | | | | |
| DESIGN | Hose & Nozzle | | | | | | | | | | | | | | | |
| MODEL NUMBER | 790 | 791 | 792 | 793 | 794 | 795 | 796 | 711 | 713 | 714 | 715 | 712 | 716 | 717 | 718 | |
| UL & ULC RATING | 2A:40B:C | 4A:40B:C | 4A:40B:C | 40B:C | 40B:C | 20B:C | 40B:C | 4A:80B:C | 4A:80B:C | 10A:120B:C | 10A:160B:C | 80B:C | 80B:C | 120B:C | 160B:C | |
| CAPACITY (LBS. / KG) | 13.2 / 6 | 20 / 9 | 30 / 13.6 | 13.2 / 6 | 20 / 9 | 20 / 9 | 30 / 13.6 | 10 / 4.5 | 13.2 / 6 | 20 / 9 | 30 / 13.6 | 10 / 4.5 | 13.2 / 6 | 20 / 9 | 30 / 13.6 | |
| *SHIPPING WT. (LBS.) | 29 | 40 | 56 | 29 | 40 | 40 | 56 | 19.5 | 29 | 40 | 56 | 19.5 | 29 | 40 | 56 | |
| HEIGHT (IN.) | 17.5 | 24.75 | 26.5 | 17.5 | 24.75 | 24.75 | 26.5 | 20.5 | 17.5 | 24.75 | 26.5 | 20.5 | 17.5 | 24.75 | 26.5 | |
| WIDTH (IN.) | 10.5 | 10.5 | 11 | 10.5 | 10.5 | 10.5 | 11 | 8.25 | 10.5 | 10.5 | 11 | 8.25 | 10.5 | 10.5 | 11 | |
| DEPTH (IN.) | 7 | 7 | 8 | 7 | 7 | 7 | 8 | 5 | 7 | 7 | 8 | 5 | 7 | 7 | 8 | |
| RANGE (INITIAL- FT.) | 40-50 | | | | 40-50 | | | | 15-21 | | 40-50 | | 15-21 | | 40-50 | |
| DISCHARGE TIME (SEC.) | 15 | 18 | 21 | 15 | 15 | 10 | 16 | 22 | 22 | 30 | 34 | 22 | 22 | 29 | 34 | |
| AVERAGE DISCHARGE RATE (LBS. / SEC.) | .94 | 1.20 | 1.60 | .94 | 1.44 | 2.00 | 1.88 | 0.5 | .59 | .65 | .95 | 0.45 | .61 | .67 | .81 | |
| NOMINAL OPERATING PRESSURE | 240 PSIG | 240 PSIG | 240 PSIG | 240 PSIG | 240 PSIG | 240 PSIG | 240 PSIG | 195 PSIG | 240 PSIG | 240 PSIG | 240 PSIG | 195 PSIG | 240 PSIG | 240 PSIG | 240 PSIG | |
| INCLUDED BRACKET | Wall | | | | Wall | | | | Wall | | | | Wall | | | |

*Shipping weight includes box.

